

Stripe configs

1/ Frans uses Stripe in Pre-auth mode. Make sure your localhost environment also uses Pre-auth mode. In config, change `Payment action` to `Authorize Only`:


stripe Stripe
Accept online payments using Stripe, the platform of choice of forward-thinking businesses around the world.

⊙ General settings

⊙ Payments

Enabled [store view] Yes

Payment flow [store view] Embed payment form into the native flow.

 With the embedded payment flow, an iframe-based [Payment Element](#) is displayed directly on your Magento checkout page.

Form layout [store view] Vertical - Accordion
View example layouts at stripe.com/docs/payments/payment-element.

Title [store view] Credit Card
This is the payment method title used at the checkout page.

Payment method configuration [store view] Disabled
Enable/disable payment methods. [Configure](#)

Payment action [store view] Authorize Only

2/ To debug local stripe connect (local webhook):

Install Stripe CLI

In command line, enter `stripe listen --forward-to http://sfran/stripe/webhooks`

Stripe cli will inform the webhook secret, such as:

```

```
> Ready! You are using Stripe API Version [2016-02-23]. Your webhook signing secret is
whsec_9980a4bbb158f30d3288c6ea85d8f085123456c97bea7abe35a8adc62e4b8d4 (^C to quit)
```

```

Copy that secret into table `stripe_webhooks`, column `secret`. Make sure that table only has 1 row; to avoid confusion.

Revision #3

Created 3 November 2024 17:18:25 by Brian

Updated 26 May 2025 15:42:58 by Brian